HEARING PROTECTION COBRA® EARMUFFS

PRODUCT DATA SHEET: EMCOB



PRODUCT CODE: EMCOB





FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 $SLC_{00}28dB$.
- Hearing protection for noise levels to 113dB(A).
- Classic green with a hi-vis orange strip.
- General purpose use.
- Solid, lightweight ear cup construction.
- High quality ear cushions.
- Inner foam & headband cushions provides comfort during extended wear.
- Low clamping force applies minimum pressure while maintaining a tight, snug seal.
- Compact folding for ease of storage.

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EMCOB	EACH	1	25

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Cobra Earmuffs - EMHKCOB.

APPLICATIONS

Insert Applications, Insert Applications.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TEST SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ









PRODUCT DETAILS

Weight: 243g Clamping Force: 11.3N Colour: Green

Size: Standard One Size

TEST DATA

ATTENUATION TABLE (ATTENTION IN DECIBELS)									
Frequency Hz	125	250	500	1000	2000	4000	8000		
Mean Attenuation	15.3	16.8	26.9	32.5	35.6	37.0	36.3		
Standard Deviation	5.0	3.2	3.5	3.2	3.6	3.8	4.3		
Mean-Minus-Standard Deviation Attenuations	10.3	13.6	23.4	29.3	32.0	33.2	32.0		

SLC₈₀ Value is 28 (Class 5)

STANDARDS

CERTIFIED TO:

 $\begin{tabular}{ll} AS/NZS~1270:2002~Acoustic~Hearing~Protectors~-\\ Class~5~SLC_{80}28dB \end{tabular}$

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 113dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.





PARAMOUNTSAFETY.COM