

HEARING PROTECTION

EARPLUG DISPENSER STATION 500 | PROBULLET™ DISPOSABLE EARPLUGS REFILL

PRODUCT DATA SHEET: EPDS500A | EPDS500R



PRODUCT CODE:
EPDS500A



PRODUCT CODE:
EPDS500R



FEATURES AND BENEFITS

EPDS500A

- Dispenser holds 500 pairs of ProBullet™ or ProBell™ Disposable Uncorded Earplugs.
 - Dispenses one pair at a time.
 - Units are sold individually with refills available in 500 pair bags for both ProBullet™ and ProBell™ uncorded disposable earplugs
- EPDS500R
- 500 uncorded pairs.
 - Refill bag compatible with the Pro Choice Safety Gear earplug dispenser station.



COMFORT



HI-VIS



HYGIENIC

PRODUCT DETAILS

Material:	PU Foam
Length:	2.8cm
Diameter:	1.2cm
Weight:	3.1g
Colour:	Hi-Vis Orange Foam

AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
EPDS500A	EACH	1	5
EPDS500R	EACH	1 BAG (500 PAIRS)	10 BAGS (5000 PAIRS)

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	24	26.0	29.7	29.6	33.9	41.4	42.0
Standard Deviation	6.3	6.7	7.3	6.1	4.6	6.6	7.3
Mean-Minus-Standard Deviation Attenuations	17.7	19.3	22.4	23.5	29.3	34.8	34.7

SLC₈₀ Value is 27 (Class 5)

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors
Class 5 SLC₈₀ 27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH25293

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077

TECH SUPPORT: 1300 275 820

CUSTOMER SERVICE: 1300 770 723

EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOLFF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013

TECH SUPPORT: 0800 888 778

CUSTOMER SERVICE: 0800 888 778

EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS