

ROUND SLING

PART CODE: **SR(CAPACITY)(LENGTH)**



LIFTING RIGGING

PRODUCT DESCRIPTION >

High tenacity, UV resistant, Round Sling.

PRODUCT FEATURES >

- Material: 100% High tenacity UV resistant polyester for extreme UV conditions.
- Working load designated by international protocol for load rating colours.
- All slings have capacity stripes woven into the sling material.
- Colour coded as per international protocol.

PRODUCT DETAILS >

- **Capacity:** 1T – 8T (10T to 100T details available on request).
- **Safety Factor** 7:1.

COLOUR CODE GUIDE >

1T	P.NO.	CAP.	LEN.	2T	P.NO.	CAP.	LEN.	3T	P.NO.	CAP.	LEN.	4T	P.NO.	CAP.	LEN.
	SR01005	1T	0.5M		SR02005	2T	0.5M		SR03005	3T	0.5M		SR04010	4T	1.0M
SR01010	1T	1.0M	SR02010	2T	1.0M	SR03010	3T	1.0M	SR04020	4T	2.0M				
SR01015	1T	1.5M	SR02015	2T	1.5M	SR03015	3T	1.5M	SR04030	4T	3.0M				
SR01020	1T	2.0M	SR02020	2T	2.0M	SR03020	3T	2.0M	SR04040	4T	4.0M				
SR01030	1T	3.0M	SR02030	2T	3.0M	SR03030	3T	3.0M	SR04050	4T	5.0M				
SR01040	1T	4.0M	SR02040	2T	4.0M	SR03040	3T	4.0M	SR04060	4T	6.0M				
SR01050	1T	5.0M	SR02050	2T	5.0M	SR03050	3T	5.0M							
SR01060	1T	6.0M	SR02060	2T	6.0M	SR03060	3T	6.0M							

5T	P.NO.	CAP.	LEN.	6T	P.NO.	CAP.	LEN.	8T	P.NO.	CAP.	LEN.
	SR05010	5T	1.0M		SR06020	6T	2.0M		SR08060	8T	6.0M
SR05020	5T	2.0M	SR06030	6T	3.0M						
SR05030	5T	3.0M	SR06040	6T	4.0M						
SR05040	5T	4.0M	SR06050	6T	5.0M						
SR05050	5T	5.0M	SR06060	6T	6.0M						
SR05060	5T	6.0M									



AS4497.1



ISO 9001
ISO 14001