

The cutting-edge RANGER delivers the absolute in stylish protection and high performance. Created to protect workers vision in the toughest of conditions, its high-contour dual-lens design ensures total outdoor protection, while its solid and rugged styling delivers a safety sunglass that looks amazing both on and off the job. Designed to suit a wide range of face shapes, it features a three-point lens inclination setting for a customised fit, co-injected thermoplastic rubber temples and nose bridge for added comfort and slip resistance. Finished in a premium soft-touch coating, the RANGER is available in a wide choice of lens options, including mirrored, smoke, polarised and Smart Vue.

KEY FEATURES

- ❖ Rugged and bold design
- ❖ Dual 8 base curve lens
- ❖ Co-injected thermoplastic rubber temples and nose bridge
- ❖ 3-point lens inclination system for customised fit
- ❖ Soft touch frame finish
- ❖ Dielectric design contains no metal parts
- ❖ Available in 6 lens options including smoke, 3 mirrored, polarised and Smart Vue (Photochromic)



| COMPONENT | SPECIFICATION | CLEANING AND STORAGE |
|---|-------------------------------|--|
| LENS | 8 base curve polycarbonate | Lenses should be cleaned on a regular basis |
| FRAME | Co-injected TPR/Polycarbonate | For best results use our Aquaclean Plus lens cleaning range |
| TEMPLE | Co-injected TPR/Polycarbonate | AC 500 (Box of 500 pre-moistened towelettes) |
| NOSE PIECE | Co-injected TPR/Polycarbonate | AC 100 (Box of 100 pre-moistened towelettes) |
| ADJUSTABILITY | 3-point lens inclination | AC 500CS (Cleaning station / 500ml spray bottle / tissues) |
| WEIGHT | 36 grams | Avoid cleaners that contain alcohol / ammonia |
| FIT | Medium/Large | All products should be kept in a clean and dry environment and placed in a microfibre pouch or carry case after each use |
| COUNTRY OF ORIGIN | Taiwan | |
| STANDARDS | | PACKAGING |
| AS/NZS 1337.1 : 2010 | | 10 pairs per inner box |
| Medium Impact | | 200 pairs per outer carton |
| Certified: SAI Global Lic 40234 | | |
| Additional Standards: ANSI Z87.1+ | | |
| For guidance and the use of occupational eye protectors refer to AS/NZS 1336.1997 | | |

VARIATIONS



| REF | FRAME | LENS TINT | LENS COATING | VLT | FILTERS | CAT | EAN |
|-------|--------------|---------------|-----------------------|-------|---------|-----|---------------|
| 840S | Frozen Black | Smoke | Anti-Fog/Anti-Scratch | 13% | 87% | 3 | 9336208008441 |
| 840BM | Frozen Black | Blue Mirror | Anti-Scratch | 13% | 87% | 3 | 9336208008465 |
| 840RM | Frozen Black | Red Mirror | Anti-Scratch | 13% | 87% | 3 | 9336208008489 |
| 840SM | Frozen Black | Silver Mirror | Anti-Scratch | 13% | 87% | 3 | 9336208008502 |
| 840P | Frozen Black | Polarised | Anti-Scratch | 13% | 87% | 3 | 9336208008526 |
| 840SV | Frozen Black | Smart Vue | Anti-Scratch | 82-12 | 8%-88% | 0-3 | 9336208008540 |