

ULTRA-BUND®



Constructed from heavy duty urethane, Ultra-bund® is built tough to withstand the rigors of both light and heavy workshop / warehouse traffic. Ideal for installing across doorways or creating your own customised secondary containment area within your workshop.



Floor bunding that's truly durable...

Floor bunding is a cost effective way of meeting your secondary containment requirements, where hazardous substances are stored and used. Best practice is to provide a permanent bunding solution that stops liquids leaving your workshop or warehouse. Ultra-bund® is permanently attached to the floor with a strong sealant/adhesive and dynabolts. Its rugged construction means it can withstand all types of workshop traffic including pneumatic and solid wheels. The curved profile reduces load disturbance when crossing the bund and channelling across the top of the Ultra-bund® reduces slippage.



Ultra-bund® is easy to install. Pre-moulded corners are available to allow for installation in virtually any configuration. In addition, installation components including, sealant/adhesive, dynabolts and spacers are available as a kit or as individual components.



Ultra-bund® Products available:

Ultra-bund® 150mm x 25mm x 1m - Code: STDB150



Ultra-bund® 200mm x 32mm x 1m - Code: STDB200



Ultra-bund® 90° Corner Pieces



Code:
STDB150CNR



Code:
STDB200CNR



Ultra-bund® Installation Kit:
Includes instructions plus enough sealant / adhesive, dynabolts and spacers to install 5m of **Ultra-bund®**

Components can also be purchased separately.



To find a SpillTech Ultra-Bund® distributor near you, contact:

DALTON INTERNATIONAL LIMITED

Physical Address: Unit 6, 23 Ash Road, Wiri, Auckland, 2104

Tel: 0800 323 223 or +64 09 263 3142 | Web: www.daltoninternational.co.nz | Email: enquiries@dilnz.co.nz