

# ALUMINIUM BUNDING



## Product Dimensions

Product	Code	Length	Width	Height
Aluminium Bunding	STAB33	1200ml	184mm	30mm
Installation Kit	STAB33-IK			
(4 x Concrete Bolts, 1 x 300g Tube Adhesive / Sealant and Instructions)				



### APPLICATION EXAMPLES

Industrial areas with heavy duty machinery  
High frequency traffic areas  
Class 3 Flammable liquid storage areas  
Warehouses, doorways and access points  
Wash Bays

### FIRE RESISTANT

Aluminium Floor Bunding is a unique product ideal for flammable liquid containment in accordance with safety legislation AS 1940-2004 "A spillage containment compound shall be sufficiently impervious to retain spillage and to enable recovery of any such spillage. The compound shall be chemically resistant and fire resistant as far as is necessary to fulfil its locations." Aluminium is non-magnetic and nonsparking, therefore suitable where explosive vapour mixtures are present.

### PERMANENT

Aluminium bunding will offer similar longevity to concrete bunds but at a fraction of the price. Install it once and it will protect your site for many years to come.

### TOUGH

This solid and robust bund, made from marine grade extruded aluminium, withstands frequent and heavy traffic over a long period of time. The aluminium bund is suitable for heavy vehicles such as Class 2 RAV B-Doubles and heavy duty container forklifts.

### PRACTICAL

The grooves provide traction as the vehicle passes over the low profile bund. The 30mm height provides bunding capacity while the profile maximizes clearance and allows easy vehicle passage with minimal driver discomfort.

### STRAIGHTFORWARD INSTALLATION

The standard aluminium bund comes in predrilled 1200mm long sections. The installation kit includes concrete fasteners and adhesive sealant. Cutting is available at additional charge for mitre corners and custom lengths.