



Product Code: PS-EPOU-10 | PS-EPOU-50

PROBULLET™ DISPOSABLE EARPLUGS UNCORDED | 10 PACK | 50 PACK



FEATURES & BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 SLC₈₀27dB.
- Hearing protection for noise levels to 110dB(A).
- Hi-vis orange for visual identification & compliance.
- Economical & convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage.
- Smooth tapered shape for easy insertion into the ear canal.
- Range of pack sizes & dispensing options.
- Refill bag compatible with the Pro Choice Safety Gear dispenser station.



**PRODUCT CODE:
PS-EPOU-10**



**PRODUCT CODE:
PS-EPOU-50**



PRODUCT DETAILS

Material: PU Foam
Length: 2.8cm
Diameter: 1.2cm
Weight: 3.1g
Colour: Hi-Vis Orange Foam

AVAILABLE IN:

| PRODUCT CODE | UOM | MOQ | CTN QTY |
|--------------|------|-------------------|------------------------|
| EPOU-10 | BOX | 1 BOX (10 PAIRS) | 200 BOXES (2000 PAIRS) |
| EPOU-50 | PACK | 1 PACK (50 PAIRS) | 100 PACKS (5000 PAIRS) |

STANDARDS:

CERTIFIED TO:

AS/NZS 1270:2002 Acoustic Hearing Protectors Class 5 SLC₈₀27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

APPLICATIONS:

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.

TEST DATA:

| ATTENUATION TABLE (ATTENUATION IN DECIBELS) | | | | | | | |
|---|------|------|------|------|------|------|------|
| Frequency Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
| Mean Attenuation | 24.0 | 26.0 | 29.7 | 29.6 | 33.9 | 41.4 | 42.0 |
| Standard Deviation | 6.3 | 6.7 | 7.3 | 6.1 | 4.6 | 6.6 | 7.3 |
| Mean-Minus-Standard Deviation Attenuations | 17.7 | 19.3 | 22.4 | 23.5 | 29.3 | 34.8 | 34.7 |

SLC₈₀ Value is 27 (Class 5)

