



Product Code: PS-EPYU | PS-EPYC  
**PROBELL™ DISPOSABLE  
 EARPLUGS**  
**| CORDED & UNCORDED**



### FEATURES & BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC<sub>80</sub>27dB.
- Hearing protection for noise levels to 112dB(A).
- Hi-vis yellow for visual identification & compliance.
- Economical & convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage.
- Bell shape provides maximum comfort.
- Design makes it easier to insert & reduces tendency to back out of the ear.
- Pairs packaged in individual poly bags.
- Refill bag compatible with the Pro Choice Safety Gear dispenser station.



**PRODUCT CODE:  
PS-EPYU**



**PRODUCT CODE:  
PS-EPYC**



COMFORT



HI-VIS



HYGIENIC

### PRODUCT DETAILS

**Material:** PU Foam  
**Length:** 2.5cm  
**Diameter:** 1.6cm  
**Colour:** Hi-Vis Orange Foam  
 Blue Cord

**AVAILABLE IN:**

PRODUCT CODE	UOM	MOQ	CTN QTY
EPYU	EACH	1	10
EPYC	EACH	1	10

### STANDARDS:

CERTIFIED TO:

**AS/NZS 1270:2002** Acoustic Hearing Protectors Class 5 SLC<sub>80</sub>27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 112dB(A) assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

### APPLICATIONS:

Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.

### TEST DATA:

ATTENUATION TABLE (ATTENUATION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	22.9	25.5	29.8	30.0	32.4	40.1	40.1
Standard Deviation	6.5	6.3	7.0	6.8	4.9	6.6	7.0
Mean-Minus-Standard Deviation Attenuations	16.4	19.2	22.8	23.2	27.5	33.5	33.1

SLC<sub>80</sub> Value is 27 (Class 5)

